

PRODUCT DATA SHEET



HIGHBUILD SEAL

DESCRIPTION

COLORO HIGHBUILD SEALER is a high solids solventbased sealer system designed to be used on Stencil, Stamped Concrete, Garden Edging, Exposed Aggregate etc.

COLORO HIGHBUILD SEALER should be applied to the surface with a low-pressure spray, broom, or roller.

DIRECTIONS

Do not apply in temperatures below 5degC. or above 30deg C.

Apply with a Spray, Broom or Roller at the rate of 2-5m2/Litre.

Do NOT apply on wet concrete WAIT until the concrete has cured OR apply over 1 coat of same day sealer, 7-14 days after the 1st coat.

Do NOT use on glazed or semi glazed tiles without special preparation.

Apply 1-3 coats.

Application of each subsequent coat should be at right angles to the previous.

Apply a third coat if gloss level not high enough.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, do NOT induce vomiting.

If in eyes, hold eyes open. flood with water for at least 15 minutes and see a doctor.

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

COVERAGE

2-5m2/Litre

CLEAN UP

Wash up with Xylene

STORAGE

Product is Class 3 Dangerous Good & should be stored as specified in AS1940.

Keep in a cool dry place, away from ignition sources and away from incompatible chemicals.

PACKS

20L, 200L.

COLORO HIGHBUILD SEAL PDS - July 2020

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Chemical House does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether in accordance with any advice, specification, recommendation, or information given by it.

CHEMICAL HOUSE

Headquarters 9 Production Avenue, Molendinar Queensland, 4214 Australia 0Ph: +61 7 5594 0344 www.chemicalhouse.com.au





