



GREEN RELEASE AGENT

DESCRIPTION

GREEN RELEASE AGENT is a blend of oils, and resins finding use on steel shutters as a mould-release agent.

It is not designed as a Tilt-up Slab release.

Use the specific product. The carrying solvent for GREEN RELEASE AGENT functions as a release agent, and its action is boosted by the presence of selected resins.

GREEN RELEASE AGENT is not classified as flammable, however classified under AS1940 as combustible.

GREEN RELEASE AGENT is based on environmentally green, renewable materials and consequently biodegradable.

GREEN RELEASE AGENT meets the Green Star- Office Design V3 Ieq-13 specifications.

DIRECTIONS

Apply GREEN RELEASE AGENT on timber formwork or steel shutters at a rate of 10-20m²/L and apply two coats coating North-South & East-West.

GREEN RELEASE AGENT does not dry fully, being like diesel-based release agents.

GREEN RELEASE AGENT can be used on concrete surfaces, but must only be applied on a damp surface, as it will penetrate too far into the surface to be effective.

If the preparation is damaged by rain, test for presence by checking for water beading.

Re-apply if not evident.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre.

If swallowed do NOT induce vomiting.

Give a glass of water.

If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

STORAGE

Any spills should be absorbed with sand /soil recovered into a mild steel drum and disposed in line with government regulations.

PACKS

20L, 200L

GREEN RELEASE AGENT - PDS MAY 2023

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Chemical House does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether in accordance with any advice, specification, recommendation, or information given by it.

CHEMICAL HOUSE

Headquarters

9 Production Avenue, Molendinar

Queensland, 4214 Australia

Ph: +61 7 5594 0344

www.chemicalhouse.com.au