## CHEMICAL HOUSE®

CHEMISTRY HOUSE PTY LTD **9 Production Avenue** Molendinar. Qld 4214

PRODUCT:

ACN 610 881 153

"from our house to yours"

)+61-7-55940344 昌 +61-7-55940236 1:info@chemicalhouse.com.au

PO BOX 595 ASHMORE CITY, QLD. 4214



STRIPCHIEF-2 (EP9091) is a gel-type non-methylene chloride based, water **DESCRIPTION:** clean-up stripper specifically designed for stripping varnish, enamels, acrylic paints; in fact **STRIPCHIEF-2** is suitable for use on most paint systems including, Anti-foul, 2-pack epoxies, and 2-pack or moisture-cure urethanes. STRIPCHIEF-2 is also suitable for cleaning up brushes, and rollers. STRIPCHIEF-2 contains selected ingredients to emulsify the stripped coating, allowing a water wash off. Ideal for graffiti removal off masonry and timber surface.

STRIPCHIEF-2 is a low odour formula and is now considered hazardous (GHS-Global Harmonised System) however has low toxicity. As before, normal good industrial practice should be adhered to i.e. use of gloves and eye protection as a very minimum. Do NOT use in confined spaces.

STRIPCHIEF-2 has a longer /lopen time" than conventional solvent strippers, allowing for a deeper penetration/to be achieved, facilitating full thickness coating. Providing application thickness is ca 5mm STRIPCHIEF-2 will remain open and active for up to 24 hours.

SURFACE PREPARATION:

**DIRECTIONS FOR USE :** 

Ensure the STRIPCHIEF-2 is well mixed; open can away from face.

Apply over the surface to be removed, using a brush (natural bristle not synthetic bristles). Apply a coating at least 1-5 mm thick and allow to work. When blistering is evident scrape or wash off with clean water. Repeat if necessary if full thickness removal not achieved. For difficult coating removal the use of several layers of newspaper placed on top of the applied stripper to trap the solvent on the surface longer is effective. 1-/2m²/L

Coverage

Clean Up

Caution:

FIRST AID:

Water if still open and gel-like.

Surface to be dry.

Do not allow to come in contact with mobile telephones, ABS or acrylic plastics.

If poisoning occurs, contact a doctor or Poisons Information Centre 131126. If swallowed do NOT induce vomiting. Give a glass of water. If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

Not classified as a dangerous substance for purpose of transport. Not to be STORAGE: loaded with Oxidising Agents (Class 5), or Foodstuffs. Store in cool well ventilated area. A \$afety Data Sheet is available.

SAFETY PACKS: Ref:Strip Chief-2 pds Date: March 18

1L, 5L, 20L, 200L.