

PRODUCT:**EASI-ORANGE****DESCRIPTION:**

For use as a dewaxing solvent for removal of travel wax, bitumen based coatings, asphalt, inks, acrylic coatings etc. **EASI-ORANGE** is emulsifiable in water and forms a QUIK BREAK emulsion, allowing for recovery of the oil phase into recovery containers. Can be used as a concentrate for general purpose degreaser in the engine bay or similar when prediluted 1-10 with keroor water.

DIRECTIONS FOR USE :

Apply neat or at the pretested diluted rate to a dry surface, agitate, allow to work, rinse off with low or high pressure water. Collect rinsings to allow recovery / separation of the oil phase or dispose only via sewage system.

RISK PHRASES:

R 38 Irritating to skin. R 43 May cause sensitisation by skin contact.

SAFETY PHRASES:

S 24 Avoid contact with skin. S 37 Wear suitable gloves. S 60: This material and its container must be disposed of as hazardous waste. S 61: Avoid release to the environment. (refers to undiluted product) Refer to special instructions/safety data sheets.

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre 131126. If swallowed, do NOT induce vomiting. Give glass of water. If skin contact occurs, remove contaminated clothing and wash skin thoroughly. Remove from contaminated area. Apply artificial respiration if not breathing. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

STORAGE:

Not classed Flammable. Store in a cool dry place, away from naked flames, ignition points and incompatible compounds.

DISPOSAL:

Easi Orange suitably diluted with water (1+10) is biodegradable.

PACKS:

4L, 10L, 20L, 200L

Ref:EASI-ORANGE_pds.doc

Date:April 2011