

# CHEMICAL HOUSE®

PTY LTD

ACN 010418 569

9 Production Avenue  
Molendinar. Qld 4214

*"from our house to yours"®*

+61-7-55940344

+61-7-55940236

PO BOX 595 ASHMORE CITY, QLD. 4214

info@chemicalhouse.com.au

## PRODUCT:

## ENVIRO- RELEASE OIL (EP2017)

## DESCRIPTION:

**ENVIRO-RELEASE OIL** is a blend of oils, and resins finding use on timber forms **and** steel shutters as a release agent. It is not designed as a Tilt-up Slab release. Use the specific product. The carrying solvent for **ENVIRO-RELEASE OIL** functions as a release agent, and its action is boosted by the presence of 'shower resistant' additives. **ENVIRO-RELEASE OIL** is not classified as flammable, it however classified under AS1940 as combustible.

**ENVIRO-RELEASE OIL** is based on environmentally green, renewable materials and consequently biodegradable. **ENVIRO-RELEASE OIL** meets the Green Star- Office Design V3 leq-13 specifications.

## DIRECTIONS FOR USE :

Apply **ENVIRO-RELEASE OIL** on timber formwork or steel shutters at a rate of 5-10m<sup>2</sup>/L and apply two coats coating North-South & East-West. **ENVIRO-RELEASE OIL** does not dry fully, being similar to diesel based release agents. **ENVIRO-RELEASE OIL** can be used on concrete surfaces, but must only be applied on a damp surface, as it will penetrate too far into the surface to be effective. If the preparation is damaged by rain, test for presence by checking for water beading. Re-apply if not evident.

## FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed do NOT induce vomiting. Give a glass of water. If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

## STORAGE:

Any spills should be absorbed with sand /soil recovered into a mild steel drum and disposed in line with government regulations.

## PACKS:

20L, 200L

Ref:ENVIRO-RELEASEOIL\_EP2017\_pds.doc  
Date:Jan 2010.